

SPECIFICATIONS:

Model#	No. Lamps	KW @ 120V	AMP @ 120V	Pipe Size	Overall Dimensions L x W x D	Wetted Material	Shipping Weight
AS - V16	1	0.17	1	1.5"	47.5" x 10" x 17"	304 SS	35 lbs.
AS - V26	2	0.33	2	2"	47.5" x 11.25" x 17"	304 SS	45 lbs.
AS - V36	3	0.49	3	3"	47.5" x 11.25" x 17"	304 SS	60 lbs.
AS - V38	3	0.49	3	3"	47.5" x 12" x 19"	304 SS	98 lbs.
AS - V48	4	0.66	4	4"	47.5" x 12" x 19"	304 SS	105 lbs.
AS - V58	5	0.83	5	4"	47.5" x 12" x 19"	304 SS	165 lbs.
AS - V510	5	0.83	5	4"	47.5" x 14" x 21"	304 SS	45 lbs.
AS - V610	6	0.97	6	6"	47.5" x 14" x 21"	304 SS	60 lbs.
AS - V612	6	0.97	6	6"	47.5" x 16" x 21"	304 SS	98 lbs.
AS - V810	8	1.3	8	6"	47.5" x 16" x 21"	304 SS	105 lbs.
AS - V812	8	1.3	8	6"	47.5" x 16" x 23"	304 SS	165 lbs.

ULTRAVIOLET DOSAGE:

Model#	Flow = GPM @30K EOL	Flow = GPM @40K EOL	Flow = GPM @30K EOL	Flow = GPM @90K EOL	Flow = GPM @300K EOL
AS - V16	59	44	63	21	6
AS - V26	115	86	121	40	12
AS - V36	167	125	175	58	17
AS - V38	233	175	246	82	24
AS - V48	305	228	321	107	32
AS - V58	373	280	393	131	39
AS - V510	484	363	510	170	51
AS - V610	574	430	604	201	60
AS - V612	705	529	743	247	74
AS - V810	745	559	785	261	78
AS - V812	924	693	973	324	97

COLOR KEY:

Clear Fresh Water at 94% UVT	DI / RO Water (-03D) at 99% UVT
DI / RO Water at 99% UVT	DI / RO Water (TOCR) at 99% UVT

NOTES: 220V Specs are available upon request

